

**ARALDITE® MY 790-1 US**

Version 1.0      Revision Date: 10/20/2016      SDS Number: 400001009665      Date of last issue: -  
Date of first issue: 10/20/2016

**SECTION 1. IDENTIFICATION**

Product name : ARALDITE® MY 790-1 US

**Manufacturer or supplier's details**

Company name of supplier : Huntsman Advanced Materials Americas LLC  
Address : P.O. Box 4980  
The Woodlands,  
TX 77387  
United States of America  
Telephone : Non-Emergency: (800) 257-5547  
E-mail address of person responsible for the SDS : MSDS@huntsman.com  
Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

**Recommended use of the chemical and restrictions on use**

Recommended use : Component used for the manufacture of electrical insulation parts

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitisation : Category 1  
Acute aquatic toxicity : Category 2  
Chronic aquatic toxicity : Category 2

**GHS label elements**

Hazard pictograms : 

Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

P264 Wash skin thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P391 Collect spillage.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Substance

**Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Bisphenol A epoxy resin	25068-38-6	95 - 100

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : None known.

Notes to physician : No information available.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : No data is available on the product itself.

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No data is available on the product itself.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Strong acids  
  
Strong bases  
  
Strong oxidizing agents
- Recommended storage temperature : 18 - 40 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

## Hand protection

Material : butyl-rubber

Break through time : > 8 h

Solvent-resistant gloves (butyl-rubber)

Nitrile rubber

10 - 480 min

Neoprene gloves

Remarks : The suitability for a specific workplace should be discussed

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

- with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Colour : colourless
- Odour : slight
- Odour Threshold : No data is available on the product itself.
- pH : No data is available on the product itself.
- Melting point/freezing point : No data available
- Boiling point : > 200 °C
- Flash point : > 150 °C Method: Information given is based on data obtained from similar substances., closed cup
- Evaporation rate : No data is available on the product itself.
- Flammability (solid, gas) : No data is available on the product itself.
- Flammability (liquids) : No data is available on the product itself.
- Upper explosion limit : No data is available on the product itself.
- Lower explosion limit : No data is available on the product itself.
- Vapour pressure : No data is available on the product itself.
- Relative vapour density : No data is available on the product itself.
- Relative density : No data is available on the product itself.
- Density : 1.15 - 1.2 g/cm<sup>3</sup> (25 °C)
- Solubility(ies)  
Water solubility : insoluble (20 °C)

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C  
Method: Information given is based on data obtained from similar substances.

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

Viscosity : No data is available on the product itself.

Molecular weight : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.  
No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : Burning produces noxious and toxic fumes.  
Carbon oxides

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : No data is available on the product itself.

**Acute toxicity****Components:**

Bisphenol A epoxy resin:

Acute oral toxicityComponents : LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

**Components:**

Bisphenol A epoxy resin:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

Assessment: No data available

**Germ cell mutagenicity****Components:**

Bisphenol A epoxy resin:  
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: positive

Concentration: 0 - 5000 ug/plate  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: positive

**Components:**

Bisphenol A epoxy resin:  
Genotoxicity in vivo : Cell type: Germ  
Application Route: Oral  
Method: OECD Test Guideline 478  
Result: negative

Cell type: Somatic  
Application Route: Oral  
Dose: 0 - 5000 mg/kg  
Method: OPPTS 870.5395  
Result: negative

**Components:**

Bisphenol A epoxy resin:

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Germ cell mutagenicity-  
Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Germ cell mutagenicity-  
Assessment : No data available

**Carcinogenicity****Components:**

Bisphenol A epoxy resin:  
Species: Rat, (male and female)  
Application Route: Oral  
Exposure time: 24 month(s)  
Dose: 15 mg/kg  
Frequency of Treatment: 7 days/week  
Method: OECD Test Guideline 453  
Result: negative

Species: Mouse, (male)  
Application Route: Dermal  
Exposure time: 24 month(s)  
Dose: 0.1 mg/kg  
Frequency of Treatment: 3 days/week  
Method: OECD Test Guideline 453  
Result: negative

Species: Rat, (female)  
Application Route: Dermal  
Exposure time: 24 month(s)  
Dose: 1 mg/kg  
Frequency of Treatment: 5 days/week  
Method: OECD Test Guideline 453  
Result: negative

Carcinogenicity -  
Assessment : No data available

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Components:**

Bisphenol A epoxy resin:  
Effects on fertility : Test Type: Two-generation study  
Species: Rat, male and female

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Application Route: Oral  
Dose: >750 milligram per kilogram  
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight  
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight  
Symptoms: No adverse effects  
Method: OECD Test Guideline 416  
Result: No effects on fertility and early embryonic development were detected.

**Components:**

Bisphenol A epoxy resin:  
Effects on foetal  
development

: Species: Rabbit, female  
Application Route: Dermal  
General Toxicity Maternal: No observed adverse effect level:  
30 mg/kg body weight  
Method: Other guidelines  
Result: No teratogenic effects

Species: Rabbit, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
60 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Species: Rat, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
180 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Repeated dose toxicity****Components:**

Bisphenol A epoxy resin:  
Species: Rat, male and female  
NOAEL: 50 mg/kg  
Application Route: Ingestion  
Exposure time: 14 Weeks  
Number of exposures: 7 d  
Method: Subchronic toxicity

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Species: Rat, male and female  
NOEL: 10 mg/kg  
Application Route: Skin contact  
Exposure time: 13 Weeks  
Number of exposures: 5 d  
Method: Subchronic toxicity

Species: Mouse, male  
NOAEL: 100 mg/kg  
Application Route: Skin contact  
Exposure time: 13 Weeks  
Number of exposures: 3 d  
Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

**Aspiration toxicity**

No data available

**Experience with human exposure**

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

**Toxicology, Metabolism, Distribution**

No data available

**Neurological effects**

No data available

**Further information****Product:**

Remarks: No data available

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:**

Bisphenol A epoxy resin:  
Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203

**Components:**

Bisphenol A epoxy resin:  
Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.7 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Test Type: static test  
Test substance: Fresh water

**Components:**

Bisphenol A epoxy resin:  
Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: EPA-660/3-75-009

M-Factor (Acute aquatic toxicity) : No data available

Toxicity to fish (Chronic toxicity) : No data available

**Components:**

Bisphenol A epoxy resin:  
Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.3 mg/l  
aquatic invertebrates : Exposure time: 21 d  
(Chronic toxicity) : Test Type: semi-static test  
Test substance: Fresh water  
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : No data available

**Components:**

Bisphenol A epoxy resin:  
Toxicity to bacteria : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water

Toxicity to soil dwelling : No data available

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

organisms

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment  
Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Further information:  
No data available

**Persistence and degradability****Components:**

Bisphenol A epoxy resin:

Biodegradability : Inoculum: Sewage (STP effluent)  
Concentration: 20 mg/l  
Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

**Components:**

Bisphenol A epoxy resin:

Stability in water : Degradation half life(DT50): 4.83 d (25 °C) pH: 4

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life(DT50): 7.1 d (25 °C) pH: 9  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life(DT50): 3.58 d (25 °C) pH: 7  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

**Bioaccumulative potential****Components:**

Bisphenol A epoxy resin:  
Bioaccumulation : Bioconcentration factor (BCF): 31  
Remarks: Does not bioaccumulate.

**Components:**

Bisphenol A epoxy resin:  
Partition coefficient: n-octanol/water : log Pow: 3.242 (25 °C)  
pH: 7.1  
Method: OECD Test Guideline 117

**Mobility in soil**

Mobility : No data available

**Components:**

Bisphenol A epoxy resin:  
Distribution among environmental compartments : Koc: 445  
Stability in soil : No data available

**Other adverse effects**

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

**Hazardous to the ozone layer**

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of  
unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International Regulation****IATA**

UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(BISPHENOL A EPOXY RESIN)  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

**IMDG**

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(BISPHENOL A EPOXY RESIN)

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****DOT Classification**

UN/ID/NA number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes(BISPHENOL A EPOXY RESIN)

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act**

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**California Prop. 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

CH INV	: The formulation contains substances listed on the Swiss Inventory, On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

**ARALDITE® MY 790-1 US**

Version 1.0      Revision Date: 10/20/2016      SDS Number: 400001009665      Date of last issue: -  
 Date of first issue: 10/20/2016

TCSI : On the inventory, or in compliance with the inventory

**Inventories**


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**TSCA - 5(a) Significant New Use Rule List of Chemicals**

No substances are subject to a Significant New Use Rule.

**US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)**

No substances are subject to TSCA 12(b) export notification requirements.

**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

Revision Date : 10/20/2016

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

**ARALDITE® MY 790-1 US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2016	400001009665	Date of first issue: 10/20/2016

---

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.