



Bostik® SuperTak® Aerosol Adhesives are top performance adhesives neatly packaged into easy-to-handle and easy-to-store aerosol containers. These products offer a wide range of performance characteristics to choose from for consistently reliable bonds. Their versatility means SuperTak adhesives are ideal for a variety of industrial applications including assembly operations, maintenance jobs and packaging.

Each Bostik SuperTak Aerosol Adhesive has been formulated without ozone depleting chemicals or chlorofluorocarbons (CFC's).

**All SuperTak® Products Meet or Exceed
Federal and Local VOC Limits.**

SuperTak® Aerosol Adhesives



The Adhesive Company

Properties of Bostik® SuperTak® Aerosol Adhesives

	LACE PATTERN			MISTING PATTERN	
	High Performance	Trim Adhesive	Foam & Fabric	Mist	General Purpose
Features	Strong One-surface bonds High tack strength	Strong One-surface bonds	Non-dimpling Soft glue lines	Temporary or permanent bonds High initial tack	Temporary or permanent bonds Good initial grab
Recommended Uses	Permanent bonding of: • Liner • Insulation • Carpets	Permanent bonding of: • Insulation • Carpet • Foam	Bonding fabric to: • Latex • Urethane • Foams	Permanent bonding of: • Insulation • Carpet • Closed cell foam	All-purpose bonding Secure bonding of lightweight materials
Spray Pattern	Adjustable lace	Controlled lace	Controlled lace	Fine mist	Fine mist
Adjustable Nozzle Varies Lace Width	Yes	No	No	No	No
Color	Translucent	Translucent	Orange	Translucent	Translucent
Container Size	23.8 fl. oz. 17 oz. Nt. Wt.	22 fl. oz. 16. oz. Nt. Wt.	23.8 fl. oz. 17 oz. Nt. Wt.	22.8 fl. oz. 16.5 oz. Nt. Wt.	23.8 fl. oz. 17 oz. Nt. Wt.
Propellant	HC/DME	HC/DME	HC/DME	HC/DME	HC/DME
Solvent System	Hexane/Acetone	Hexane/Acetone	ISO Hexane/Acetone	ISO Hexane/Acetone	Hexane/Acetone
Delivery Rate, (g/min., 15 sec. test)	110 ± 20	97 ±20	97 ±20	70 ±15	108 ±20
Coverage, ft2 (actual)	161	157	157	159	160
Percent (%) Solids	20%	24%	20%	17%	20%
Bonding Range:					
One Surface Bonds	4 to 10 min.	1 to 5 min.	1 to 5 min.	15 sec. to 5 min.	1 to 5 min.
Two Surface Bonds	8 to 15 min.	1 to 10 min.	1 to 10 min.	1 min. to 10 min.	1 to 10 min.
Ultimate Shear Strength, psi	48	81	48	9.2	38
Peel, psi	2.0	9.6	6	4.6	3.3
High Initial Tack	Yes	Yes	No	Yes	No
Bonding:					
Temporary Bond	No	Yes	Yes	Yes	No
Permanent Bond	Yes	Yes	Yes	Yes	Yes
Max. Recommended Use Temp. (24 hr. exposure)	120°F	130°F	120°F	130°F	120°F
S.A.F.T. (1 lb. load)*	210°F	231°F	210°F	178°F	190°F

* "S.A.F.T." means (Shear Adhesion Failure Temperature)

NOTE: All SuperTak® Products Meet or Exceed Federal and Local VOC Limits.

Bostik, Inc.
211 Boston Street
Middleton, MA 01949-2128
Telephone: 800-7-BOSTIK
FAX: 978-750-7293
www.bostik-us.com

IMPORTANT NOTICE

All statements, technical information and recommendations set forth herein are based on tests which Bostik, Inc. believes to be reliable. However, Bostik, Inc. does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sales of this product shall be on terms and conditions set forth on Bostik's order acknowledgment. Bostik, Inc. warrants that the product conforms with Bostik, Inc. written specifications, and is free from defects. BOSTIK, INC. DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK, INC. BE LIABLE FOR DIRECT, CONSEQUENTIAL ECONOMIC OR OTHER DAMAGES.

B46_102309

High Performance

Strong, Permanent, One-Surface Bonds

Bostik® SuperTak® High Performance is the strongest, one-surface bond you can get from a Bostik aerosol adhesive. Its high tack and rapid cure makes it ideal in bonding a wide range of materials including polyethylene and polypropylene. Its controlled lace spray pattern, applies adhesive precisely where you want it without misting or overspray.

Features

- ◆ Creates permanent bonds between porous and nonporous surfaces
- ◆ Speeds product assembly
- ◆ Adheres to metals and most plastics
- ◆ High tack strength
- ◆ Forms strong, one-surface bonds
- ◆ Does not contain ozone depleting chemicals, methylene chloride or chlorofluorocarbons

Applications

- ◆ Attaching carpet, door skins, and fabric in van conversions
- ◆ Bonding swimming pool liners
- ◆ Bonding various plastics to each other
- ◆ Forms permanent bonds between porous and nonporous surfaces
- ◆ Installing insulation
- ◆ Permanently affixing name plates

Trim

Economical Trim Adhesive

Bostik® SuperTak® Trim adhesive is a transparent adhesive which offers a soft bond line, high heat resistance, and excellent green strength. It can be used for permanent or temporary bonds on porous or nonporous materials. SuperTak Trim Adhesive is suitable for bonding polyurethane or latex foam, carpets or fabrics. It also bonds well to insulation, wood, paper, leather, carpet, drywall, masonry, painted surfaces and FRP or other plastics.

Note: For nonmetallic substrates, testing of production parts in typical operating environments for compatibility is recommended.

Features

- ◆ Excellent green strength and heat resistance
- ◆ Bonds porous and nonporous surfaces
- ◆ Low soak
- ◆ Soft pliable bonds
- ◆ Does not contain ozone depleting chemicals, methylene chloride or chlorofluorocarbons

Applications

- ◆ Bonding polyurethane foam and latex foam
- ◆ Bonding carpet to foam
- ◆ Bonding insulation to wood and polyurethane
- ◆ Also bonds well to wood, paper, leather, drywall, masonry painted surface and FRP.

Foam & Fabric

Specially Developed for Upholstery Applications

Bostik® SuperTak® Foam & Fabric adhesive delivers instant tack and strong, soft bonds that won't dimple. Supple, undetectable bonds will give a pleasing finish to bonded fabric and urethane or latex foam. Its controlled lace spray pattern and low soak characteristics ensure neat application and minimal waste. Orange color allows easy visual detection of proper coverage.

Features

- ◆ Bonds flexible urethane and latex to metal, wood and plastic
- ◆ Forms non-dimpling, pliable bonds
- ◆ Low soak characteristics
- ◆ Precise spray pattern
- ◆ Orange color to ensure consistent coverage
- ◆ Does not contain ozone depleting chemicals, methylene chloride or chlorofluorocarbons

Applications

- ◆ General upholstery work
- ◆ Bonding urethane or latex foam to themselves or to fabric, wood, metal or plastic
- ◆ Bonding fabric in van and aircraft interiors
- ◆ Assembling office partitions
- ◆ Attaching foam to the inside of sample cases and computer cabinets

Note: Not recommended for use with flexible plastics such as unbacked vinyl. Bostik recommends testing all plastics for compatibility prior to use.

Note: For nonmetallic substrates, testing of production parts in typical operating environments for compatibility is recommended.

* Testing of production parts in typical operating environment for suitability is recommended.

ALL SUPERTAK® PRODUCTS MEET OR EXCEED FEDERAL AND LOCAL VOC LIMITS.

Mist

High Strength, Fine Mist Adhesive

Bostik® SuperTak® Mist provides a similar strength, one-surface bond as SuperTak High Performance, but with the ease of a mist spray. SuperTak Mist offers high tack bonds for a wide variety of substrates. Its long open-time and uniform spray pattern provides faster application and less waste.

Features

- ◆ Low soak, ideal for low porous surfaces
- ◆ Long open-time minimizes assembly problems
- ◆ Adheres to metal and most plastics
- ◆ Forms strong, one-surface bonds

Applications

- ◆ Bonding carpet to door skins
- ◆ Bonding plastics and metals
- ◆ Bonding insulation to sheet metal
- ◆ Bonding interior carpet and foam material
- ◆ Bonding labels and name plates

General Purpose

Excellent, All-Purpose, Industrial-Grade Aerosol Adhesive

Bostik® SuperTak® General Purpose with its fast, aggressive tack makes it ideal for light assembly jobs and maintenance applications. Use it for temporary or permanent bonds in a wide variety of applications.

Features

- ◆ A versatile instant tack adhesive
- ◆ Forms fast bonds to lightweight materials
- ◆ Suitable for permanent or nonpermanent bonds
- ◆ Does not contain ozone depleting chemicals, methylene chloride or chlorofluorocarbons

Applications

- ◆ Affixes labels and seals cartons
- ◆ Use in a variety of graphic arts applications
- ◆ Bond insulation to sheet metal

Contact Type

Quick Tack, High Strength Bonds

Bostik® SuperTak® Contact Type delivers the strength of contact cement with the convenience of an aerosol container. Use it for bonding dissimilar materials such as wood, metal, particle board, decorative laminates, and some plastics such as polyethylene film and polypropylene. It provides permanent, waterproof, two-surface contact bonds that are heat resistant.

Features

- ◆ One minute dry time means quick, reliable parts assembly
- ◆ Delivers permanent, waterproof bonds to porous and nonporous surfaces of dissimilar materials
- ◆ Meets MMM-A-130B requirements
- ◆ Does not contain ozone depleting chemicals, methylene chloride or chlorofluorocarbons
- ◆ Excellent resistance to oxidation and moisture

Applications

- ◆ Bonding high pressure laminates to cabinetry and shelving
- ◆ Attaching kick plates and decorative trim in furniture applications
- ◆ Bonding plastics to wood or metal in high temperature environments
- ◆ Bonding automotive trim