



CONAP® S-22

CONAP S-22 solvent and thinner is designed for dilution of CONATHANE® urethane conformal coatings for both dip and spray applications, in particular CONAP® CE-1171. CONAP S-22 complies with California EPA Rule 66.

TYPICAL PRODUCT CHARACTERISTICS

Color	Water White
Specific Gravity @ 25°C	0.90 - 0.93
Flashpoint	65°F (Closed-Cup)
Vapor Pressure @ 25°C	<10 mm (Hg)
Water Content	<0.1%
Threshold Limit Value (TLV)	100 ppm (skin)
Shelf Life @ 25°C (from date of manufacture when stored in the original, unopened containers)	24 months

HANDLING & STORAGE

CAUTION: CONAP S-22 solvent is a flammable liquid and should not be used in areas where open flames are present. Provide adequate ventilation - avoid breathing vapors or fumes. If skin contact occurs, wash immediately with soap and water.

AVAILABILITY

CONAP S-22 is available in gallon, 5-gallon, and 55-gallon drum containers.

CAUTION:

Responsible handling of Cytec Industries Inc. products requires a thorough preview of safety, health, and environmental issues prior to use. Review the Material Safety Data Sheet(s) for the specific Cytec Industries Inc. product(s) and container label information before opening containers. Ensure that employee exposure issues are understood, communicated to all workers, and controls are in place to prevent exposures above Permissible Exposure Limits (P.E.L.'s). Review safety and environmental issues to be certain controls are in place to prevent injury to employees, the community, or the environment, and ensure compliance with all applicable Federal, State, and Local laws and regulations. For assistance in this review process, please call your Cytec Industries Inc. representative or our office noted below.

www.cytec.com/conap

• Email: custinfo@cytec.com Worldwide Contact Info: www.cytec.com/conap Tel: 716.372.9650 Fax: 716.372.1594 •