

EpoPro[®] 962

LIQUID ACCELERATOR

Tertiary amine. For ambient and high temperature cure epoxy systems used for electrical insulation materials and industrial composite applications.

EpoPro 962 - Accelerator is used in combination with Epoxy Resins and Hardeners based on carboxylic acid and anhydrides . The amount of accelerator added depends on the desired pot life as well as on other processing factors, such as temperature and duration of curing . As a guideline the proportion is 0.2 – 2.0 parts by weight in 100 parts of resin .

HANDLING PROPERTIES	<u>VALUE</u>	<u>TEST METHOD</u>
<u>EpoPro 962</u>		
Appearance	Clear Color-Less Liquid	Visual
Viscosity	< 10 cps	ASTM D-2393
Tertiary Amine Content	≥ 99%	
Density	0.90 g/cm ³	ASTM E-201
Flash Point	55°C	ASTM D-92
Water Content	< 0.5%	
Vapor Pressure at 20/60°C	~3 / ~16 mbar	

Values are based on laboratory or average production results – not for specification purposes.

PACKAGING AVIALABLE

This product is available in pint, quart, 1-gallon, 2.5 and 5-gallon containers.

STORAGE GUIDELINES

EpoPro 962 should be stored between 18°C and 40°C in original container protected from direct sunlight in a dry, cool and well ventilated area, keep away from food, drink and incompatible materials. Keep container tightly closed and sealed until ready for use . Containers that have been opened must be carefully resealed and kept upright to prevent leakage . Don't store in unlabelled containers. Use appropriate containment to avoid environmental contamination .

HANDLING PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever these products are being handled and processed. For additional information please consult the corresponding material safety data sheets.

EpoPro[™] 962 - **WARNING!** In keeping with good industrial. Keep away from eyes, skin, and clothing. Wash skin and clothing thoroughly after handling. Avoid breathing vapor or mist and use with adequate ventilation. Keep containers closed when not in use. Do NOT take internally.

Product Datasheet



FIRST AID

In case of contact: **Skin** – Immediately wash skin thoroughly with mild soap and water. Remove contaminated clothing and wash before reuse. Destroy contaminated shoes and other articles made of leather. **Eyes** – Immediately flush eyes with plenty of water for 15 minutes and get prompt medical attention. **Inhalation** - Remove person to fresh air. Administer oxygen or artificial respiration if necessary. Call a physician. **Ingestion** - Do not induce vomiting. Dilute with plenty of water and contact physician immediately. Never give anything by mouth to an unconscious person.

DISCLAIMER - IMPORTANT: The following supersedes Buyer's documents. **SELLER / MANUFACTURER MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller / Manufacturer be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict liability, tort or contract arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results presented are based on controlled or laboratory work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended

Specialty Polymers & Services, Inc. (SP&S)

27822 Fremont Court

Valencia, CA 91355

www.spolymers.com

Tel: 661-294-1790

Fax: 661-294-0640

info@spolymers.com