

SAFETY DATA SHEET

EPOCAST® 89537 A US

Section 1. Identification

GHS product identifier : EPOCAST® 89537 A US
Product code : 00055301
Other means of identification : Not available.
Product type : Liquid.
Material uses : Resin for adhesive systems
Supplier's details : Huntsman Advanced Materials Americas LLC
P.O. Box 4980
The Woodlands, TX 77387

Non-Emergency phone: (800) 257-5547

e-mail address of person responsible for this SDS : MSDS@huntsman.com


Emergency telephone number (24h/7day) : Chemtrec: (800) 424-9300 or (703) 527-3887

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
AQUATIC HAZARD (LONG-TERM) - Category 2

GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.

Precautionary statements : Wear protective gloves: > 8 hours (breakthrough time): butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL). Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Collect spillage. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Dispose of contents and container in accordance

Section 2. Hazards identification

with all local, regional, national and international regulations.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Bisphenol A epoxy resin	30 - 60	25068-38-6
Glycidylether of C12-C14 alcohols	7 - 13	68609-97-2
butylphenyl glycidyl ether	3 - 7	3101-60-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Section 4. First aid measures

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : No specific treatment. Treat symptomatically. Call medical doctor or poison control center immediately if large quantities have been ingested.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

- Flash point** : Closed cup: >100°C (>212°F) [PMCC]
- Extinguishing media**
- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.
- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
Carbon monoxide
halogenated compounds
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

- Methods and materials for containment and cleaning up** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL)
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Thermal hazards** : Not available.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : White.
- Odor** : Slight
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/Freezing point** : Not available.

Section 9. Physical and chemical properties

Boiling/condensation point	: Not available.
Flash point	: Closed cup: >100°C (>212°F) [PMCC]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: <0.00001 kPa (<0.000075 mm Hg) [room temperature]
Vapor density	: Not available.
Relative density	: 0.82 to 0.93
Solubility in water	: practically insoluble
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: >200°C (>392°F)
Viscosity	: Dynamic (room temperature): 20000 mPa·s (20000 cP)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Endpoint	Species	Result
Bisphenol A epoxy resin	-	LC0 Inhalation Vapor	Rat - Male	0.00001 ppm
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rat - Male, Female	>2000 mg/kg
Glycidylether of C12-C14 alcohols	-	LD50 Oral	Rat - Female	>2000 mg/kg
	OECD 420 Acute Oral Toxicity - Fixed Dose Method			
butylphenyl glycidyl ether	-	LC0 Inhalation Vapor	Rat	>0.15 mg/l
	-	LD50 Oral	Rat - Male	30.1 ml/kg
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rat - Male, Female	>2000 mg/kg
	OECD 425 Acute	LD50 Oral	Rat - Female	>2000 mg/kg

Section 11. Toxicological information

Oral Toxicity: Up-and-Down Procedure			
--------------------------------------	--	--	--

Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Bisphenol A epoxy resin	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Mild irritant
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Mild irritant
Glycidylether of C12-C14 alcohols	-	Rabbit	Skin - Moderate irritant
	-	Rabbit	Eyes - Mild irritant
butylphenyl glycidyl ether	OECD 402 Acute Dermal Toxicity	Rat	Skin - Non-irritant.
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Non-irritant.

Conclusion/Summary

- Skin**
- : Bisphenol A epoxy resin Irritating to skin.
 - Glycidylether of C12-C14 alcohols Irritating to skin.
 - butylphenyl glycidyl ether Non-irritating to the skin.
- Eyes**
- : Bisphenol A epoxy resin Irritating to eyes.
 - Glycidylether of C12-C14 alcohols Slightly irritating to the eyes.
 - butylphenyl glycidyl ether Non-irritating to the eyes.
- Respiratory**
- : Bisphenol A epoxy resin No additional information.
 - Glycidylether of C12-C14 alcohols No additional information.
 - butylphenyl glycidyl ether No additional information.

Sensitization

Product/ingredient name	Test	Route of exposure	Species	Result
Bisphenol A epoxy resin	OECD 429 Skin Sensitization: Local Lymph Node Assay	skin	Mouse	Sensitizing
Glycidylether of C12-C14 alcohols	EPA OPPTS	skin	Guinea pig	Sensitizing
butylphenyl glycidyl ether	OECD 429 Skin Sensitization: Local Lymph Node Assay	skin	Mouse	Sensitizing

Mutagenicity

Product/ingredient name	Test	Result
Bisphenol A epoxy resin	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Positive
	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic Metabolic activation: +/-	Positive
	Experiment: In vivo	Negative

Section 11. Toxicological information

Glycidylether of C12-C14 alcohols	Subject: Mammalian-Animal Cell: Germ Experiment: In vivo	Negative
	Subject: Mammalian-Animal Cell: Somatic Experiment: In vitro	Negative
	Subject: Mammalian-Animal Metabolic activation: +/- Experiment: In vivo	Negative
butylphenyl glycidyl ether	Subject: Mammalian-Animal Cell: Somatic Metabolic activation: +/- Experiment: In vitro	Positive
	Subject: Bacteria Experiment: In vitro	Positive
	Subject: Mammalian-Animal	

Carcinogenicity

Product/ingredient name	Test	Species	Dose	Exposure	Result/Result type
Bisphenol A epoxy resin	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat - Male, Female	15 mg/kg	2 years; 7 days per week	Negative - Oral - NOAEL
	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat - Female	1 mg/kg	2 years; 5 days per week	Negative - Dermal - NOEL
	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Mouse - Male	0.1 mg/kg	2 years; 3 days per week	Negative - Dermal - NOEL

Reproductive toxicity

Product/ingredient name	Test	Species	Maternal toxicity	Fertility	Developmental effects
Bisphenol A epoxy resin	OECD 416 Two- Generation Reproduction Toxicity Study	Rat - Male, Female	Negative	Negative	Negative

Teratogenicity

Section 11. Toxicological information

Product/ingredient name	Test	Species	Result/Result type
Bisphenol A epoxy resin	OECD 414 Prenatal Developmental Toxicity Study	Rat - Female	Negative - Oral
	EPA CFR	Rabbit - Female	Negative - Dermal
	OECD 414 Prenatal Developmental Toxicity Study	Rabbit - Female	Negative - Oral
Glycidylether of C12-C14 alcohols	OECD 414 Prenatal Developmental Toxicity Study	Rat - Female	Negative - Dermal

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Section 11. Toxicological information

Potential chronic health effects

Product/ingredient name	Test	Endpoint	Species	Result
Bisphenol A epoxy resin	OECD 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Sub-chronic NOAEL Oral	Rat - Male, Female	50 mg/kg
	OECD 411 Subchronic Dermal Toxicity: 90-day Study	Sub-chronic NOEL Dermal	Rat - Male, Female	10 mg/kg
	OECD 411 Subchronic Dermal Toxicity: 90-day Study	Sub-chronic NOAEL Dermal	Mouse - Male	100 mg/kg
Glycidylether of C12-C14 alcohols	OECD 411 Subchronic Dermal Toxicity: 90-day Study	Sub-chronic NOEL Dermal	Rat - Male, Female	1 mg/kg/d

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Other information : Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
Bisphenol A epoxy resin	EPA CFR	Acute EC50	72 hours Static	Algae	9.4 mg/l
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	48 hours Static	Daphnia	1.7 mg/l
	Unknown guidelines	Acute IC50	3 hours Static	Bacteria	>100 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	1.5 mg/l
	OECD 211 <i>Daphnia Magna</i> Reproduction Test	Chronic NOEC	21 days Semi-static	Daphnia	0.3 mg/l
Glycidylether of C12-C14 alcohols	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EL50	48 hours Static	Daphnia	7.2 mg/l
	OECD 201 Alga,	Acute IC50	72 hours	Algae	843.75 mg/l

Section 12. Ecological information

butylphenyl glycidyl ether	Growth Inhibition Test OECD 209 Activated Sludge, Respiration Inhibition Test	Acute	IC50	3 hours	Bacteria	>100	mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute	LC50	96 hours	Fish	5000	mg/l
	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute	EC50	3 hours	Bacteria	>1000	mg/l
	OECD 202: Part I (Daphnia sp., Acute Immobilisation test)	Acute	EC50	48 hours	Daphnia	67.9	mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute	EbC50 (biomass)	72 hours	Algae	9	mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute	LC50	96 hours	Fish	7.5	mg/l

Persistence and degradability

Product/ingredient name	Test	Period	Result
Bisphenol A epoxy resin	OECD Derived from OECD 301F (Biodegradation Test)	28 days	5 %
Glycidylether of C12-C14 alcohols	OECD 301F Ready Biodegradability - Manometric Respirometry Test	28 days	87 %
butylphenyl glycidyl ether	OECD 301D Ready Biodegradability - Closed Bottle Test	28 days	1.1 %

Conclusion/Summary : Bisphenol A epoxy resin Not readily biodegradable.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Bisphenol A epoxy resin	Fresh water 4.83 days Fresh water 3.58 days Fresh water 7.1 days	-	Not readily
Glycidylether of C12-C14 alcohols	-	-	Readily
butylphenyl glycidyl ether	Fresh water 17 days	-	Not readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Bisphenol A epoxy resin	3.242	31	low
Glycidylether of C12-C14 alcohols	3.77	-	low
butylphenyl glycidyl ether	3.59	-	low

Mobility in soil

Not available.

Other adverse effects : No known significant effects or critical hazards.

Other ecological information

BOD5 : Not determined.

Section 12. Ecological information

COD : Not determined.

TOC : Not determined.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport information


Proper shipping name

DOT : Environmentally hazardous substance, liquid, n.o.s. (Bisphenol a epoxy resin) Marine pollutant







TDG : Environmentally hazardous substance, liquid, n.o.s. (Bisphenol a epoxy resin) Marine pollutant

IMDG : Environmentally hazardous substance, liquid, n.o.s. (Bisphenol a epoxy resin) Marine pollutant

IATA : Environmentally hazardous substance, liquid, n.o.s. (Bisphenol a epoxy resin)

Regulatory information	UN number	Classes	PG*	Label	Additional information
DOT Classification	UN3082	9	III		Marine pollutants are only regulated for bulk and vessel shipments, per 49CFR171.4 (c) Exceptions. Except when all or part of the transportation is by vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft.

Section 14. Transport information

TDG Classification	UN3082	9	III	 	-
IMDG Classification	UN3082	9	III	 	Emergency schedules (EmS) F-A S-F
IATA Classification	UN3082	9	III	 	Passenger and Cargo Aircraft Quantity limitation: 450 L Packaging instructions: 964 Cargo Aircraft Only Quantity limitation: 450 L Packaging instructions: 964

PG* : Packing group

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

United States Regulations

TSCA 8(b) inventory : All components are listed or exempted.

TSCA 5(a)2 final significant new use rule (SNUR) : No ingredients listed.

TSCA 5(e) substance consent order : No ingredients listed.

TSCA 12(b) export notification : No ingredients listed.

SARA 311/312 : Immediate (acute) health hazard

	<u>Product name</u>	<u>Concentration %</u>
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	K-37 GLASS BUBBLES (100 BOX)	18.86
	MILLED GLASS FIBRE (RM LEAD)	6

Clean Air Act - Ozone Depleting Substances (ODS) : This product does not contain nor is it manufactured with ozone depleting substances.

Section 15. Regulatory information

SARA 313 : No ingredients listed.

	<u>Ingredient name</u>	<u>%</u>	<u>Section 304 CERCLA Hazardous Substance</u>	<u>CERCLA Reportable Quantity (Lbs)</u>	<u>Product Reportable Quantity (Lbs)</u>
CERCLA Hazardous substances	1-chloro-2,3-epoxypropane	4. 70805709416909E-04	Listed		

State regulations

PENNSYLVANIA - RTK : No ingredients listed.

California Prop 65 : **WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer.
WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>
1-chloro-2,3-epoxypropane	Yes.	Yes.

Canadian regulations

CEPA DSL : At least one component is not listed.

WHMIS Classes : Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Brazil Regulations

Classification system used : Norma ABNT-NBR 14725-2:2012

International lists

Australia inventory (AICS): All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Japan inventory: At least one component is not listed.
Korea inventory: At least one component is not listed.
Malaysia Inventory (EHS Register): Not determined.
New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): At least one component is not listed.
Taiwan inventory (CSNN): Not determined.

Section 16. Other information

**Hazardous Material
Information System (U.S.A.)** :

Health	2
Flammability	1
Physical hazards	0
Personal protection	

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**National Fire Protection
Association (U.S.A.)** :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing : 6/11/2014.
Date of issue : 6/11/2014.
Date of previous issue : No previous validation.
Version : 1

📌 Indicates information that has changed from previously issued version.

EPOCAST® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more countries, but not all countries.

Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Section 16. Other information

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.