

**EpoxyLite® E 8112 Hi Temp Resin**

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

**SECTION 1. IDENTIFICATION**

Product name : EpoxyLite® E 8112 Hi Temp Resin

**Manufacturer or supplier's details**Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)Emergency telephone : INFOTRAC - 1-800-535-5053  
number**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : This product is for industrial use only. It is not intended for  
consumer use or retail sale.  
Refer to Section 15 for any restrictions that may apply**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity : Category 1 (Lungs)  
- repeated exposure  
(Inhalation)**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H350 May cause cancer.

## EpoxyLite® E 8112 Hi Temp Resin

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Modified epoxy resin

**Hazardous components**

Component	CAS-No.	Concentration (%)
Epoxy Resin	28064-14-4	>= 60 - < 80
Crystalline silica	14808-60-7	>= 10 - < 30
Epoxy Resin	25068-38-6	>= 1 - < 5

### SECTION 4. FIRST AID MEASURES

**EpoxyLite® E 8112 Hi Temp Resin**

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Unsuitable extinguishing media : High volume water jet
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

## EpoxyLite® E 8112 Hi Temp Resin

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

Keep in suitable, closed containers for disposal.  
Absorbent paper or other organic material used for cleaning up resin is a fire hazard, as heat and spontaneous combustion can occur, particularly if the resin was catalyzed. Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
The chemical reaction that cures mixed epoxy is exothermic (heat generating). If left to cure in a contained mass, such as in a mixing vessel, it can generate enough heat to melt plastic, burn skin or ignite surrounding combustible materials. The larger or thicker the epoxy mass, the more heat generated.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Crystalline silica	14808-60-7	TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
Crystalline silica		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
Crystalline silica		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
Crystalline silica		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
Crystalline silica		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH

Hazardous components without workplace control parameters

## EpoxyLite® E 8112 Hi Temp Resin

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

<b>Engineering measures</b>	: Use with adequate ventilation. All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)
<b>Personal protective equipment</b>	
Respiratory protection	: In the case of vapour formation use a respirator with an approved filter.
Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Vapour pressure	: No data available
Flash point	: > 201 °F (> 94 °C) Method: No information available. Information taken from reference works and the literature.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available

**EpoxyLite® E 8112 Hi Temp Resin**

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.3776 g/cm <sup>3</sup> (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 21 mm <sup>2</sup> /s (104 °F (40 °C))

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Hazardous decomposition products	: The by-products expected in incomplete pyrolysis or combustion of epoxy resins are mainly phenolics, CO and water.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Acute toxicity****Product:**

**EpoxyLite® E 8112 Hi Temp Resin**

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

Acute oral toxicity : Remarks: No data available

Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method**Components:****25068-38-6 Epoxy Resin:**

Acute oral toxicity : LD50 (Rat): 11,400 mg/kg

LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
GLP: yes

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): 23,400 mg/kg

LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes**Skin corrosion/irritation****Product:**

Remarks: No data available

Remarks: May cause skin irritation and/or dermatitis.

**Components:****25068-38-6 Epoxy Resin:**Species: Rabbit  
Result: Moderate skin irritationSpecies: Rabbit  
Exposure time: 4 h  
Method: OECD Test Guideline 404  
Result: Skin irritation  
GLP: yes**Serious eye damage/eye irritation****Product:**

Remarks: No data available

Remarks: May cause irreversible eye damage.

**Components:**

## EpoxyLite® E 8112 Hi Temp Resin

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

### 25068-38-6 Epoxy Resin:

Species: Rabbit

Result: Eye irritation

### Respiratory or skin sensitisation

#### Product:

Remarks: No data available

Remarks: Causes sensitisation.

#### Components:

### 25068-38-6 Epoxy Resin:

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

### Carcinogenicity

<b>IARC</b>	Group 1: Carcinogenic to humans	
	Crystalline silica	14808-60-7
<b>OSHA</b>	OSHA specifically regulated carcinogen	
	Crystalline silica	14808-60-7
<b>NTP</b>	Known to be human carcinogen	
	Crystalline silica	14808-60-7

### Repeated dose toxicity

#### Product:

Remarks: No data available

### Aspiration toxicity

#### Components:

### 25068-38-6 Epoxy Resin:

No aspiration toxicity classification

### Further information

#### Product:

Remarks: No data available

**EpoxyLite® E 8112 Hi Temp Resin**

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**Toxicity to fish :  
Remarks: No data availableToxicity to daphnia and other :  
aquatic invertebrates : Remarks: No data available**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**Regulation 40 CFR Protection of Environment; Part 82 Protection of  
Stratospheric Ozone - CAA Section 602 Class I SubstancesRemarks This product neither contains, nor was manufactured with a  
Class I or Class II ODS as defined by the U.S. Clean Air Act  
Section 602 (40 CFR 82, Subpt. A, App.A + B).Additional ecological : No data available  
information**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

: WC: SA

EPA Hazardous Waste : none  
Code(s)

Waste from residues : Do not dispose of waste into sewer.

## EpoxyLite® E 8112 Hi Temp Resin

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.  
 Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.  
 Dispose of the solid mass only if cure is complete and the mass has cooled. Follow federal, state or local disposal regulations.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 3082  
 Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
 (Epoxy resin)  
 Class : 9  
 Packing group : III  
 Labels : Miscellaneous  
 Packing instruction (cargo aircraft) : 964  
 Packing instruction (passenger aircraft) : 964

##### IMDG-Code

UN number : UN 3082  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
 N.O.S.  
 (EPOXY RESIN)  
 Marine Pollutant : (EPOXY RESIN)  
 Class : 9  
 Packing group : III  
 Labels : 9  
 EmS Code : F-A, S-F  
 Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

UN/ID/NA number : UN 3082  
 Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

## EpoxyLite® E 8112 Hi Temp Resin

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

	(Epoxy resin)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes (Epoxy resin)

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

##### SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

##### US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

## EpoxyLite® E 8112 Hi Temp Resin

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

### Massachusetts Right To Know

Crystalline silica 14808-60-7

### Pennsylvania Right To Know

Epoxy Resin 28064-14-4

Crystalline silica 14808-60-7

Epoxy Resin 25068-38-6

### New Jersey Right To Know

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : Not Applicable

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including Crystalline silica, Phenyl glycidyl ether, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The components of this product are reported in the following inventories:

TSCA : All components of this product are listed active and/or are exempt

Section 4 / 12(b) : Not applicable


Section 5 : Not applicable

Section 6 : Not applicable

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 12/06/2022

**EpoxyLite® E 8112 Hi Temp Resin**

Version 7

Revision Date 12/06/2022

Print Date 12/06/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.