



GlideCote™

Table & Tool Surface Sealant

Reduces sliding friction and hang-ups

Will not build-up even after several applications

Will not stain or effect finishing of wood

Contains no petroleum oils or silicone

Description

Regular maintenance of saw tables and receiving tables with GlideCote™ significantly reduces sliding friction on all metal, laminate, and plastic surfaces.

Product Benefits

- Eliminates “hang-ups” on sliding surfaces.
- Protects all tools and equipment from rust.
- Up to 30% slicker than paste wax.
- Easier and quicker to apply than paste wax.
- Lasts three times (3x) longer than paste wax.
- Perfect for table saw beds, drill presses, lathes, planers, band saws, miters, panel saws, and all hand tools.

Directions

Shake well before use.

To Prevent Clogging: After each use invert the container and spray until nozzle clears.

For Saw Tables: Clean surface with degreasing agent. Spray a thin even coat of GlideCote over entire surface, including table top slides and fences. Allow a few seconds to dry. Rub lightly with a clean, dry cloth.

For Best Results: Re-spray second coat and buff lightly. Re-apply GlideCote weekly or more frequently based upon work load.

For Tools: Spray a thin even coat over entire tool surface. Let dry. Buff to shine if desired. Re-apply as needed.



For simple how-to videos visit



Get the free mobile app at
<http://gettag.mobi>

DANGER! Extremely flammable. Vapor may cause flash fire. Harmful if swallowed. Inhaling vapors harmful. Skin and eye irritant. Contents under pressure. PRECAUTIONS: Because vapors may ignite explosively, prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Keep away from heat, sparks and flame. Do not smoke, extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until vapors are gone. Avoid prolonged or repeated breathing of vapors. Do not misuse by deliberately concentrating and inhaling the contents. Keep container closed when not applying. Wear gloves and eye goggles; avoid contact with skin and eyes. Store in a cool, dry, well-ventilated area away from sunlight. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. FIRST AID: If inhaled, move person to non-contaminated air and give artificial respiration if person is not breathing. Call physician immediately if swallowed; do not induce vomiting. If contacted in eyes, flush with water for at least 15 minutes and seek medical attention. For skin contact, wash immediately with soap and water.

The Limited Warranty for this product can be obtained at www.bostik-us.com/resource-center/warranties or by calling 1-800-726-7845 (choose option 2, then option 2 again). TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

Bostik, Inc.

11320 Watertown Plank Road
Wauwatosa, WI 53226
414-774-2250
1-800-726-7845
www.bostik-us.com
www.bostikdiy.com

This document supercedes all previously published literature.

Y11- 02-17-2012