

# SAFETY DATA SHEET

## HARDENER HV 1253 US

### Section 1. Identification

**GHS product identifier** : HARDENER HV 1253 US  
**Product code** : 00048725  
**Other means of identification** : Not available.  
**Product type** : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Not available.

##### Uses advised against

Not available.

##### Reason

-

**Supplier's details** : Huntsman Advanced Materials Americas LLC  
P.O. Box 4980  
The Woodlands, TX 77387

Non-Emergency phone: (800) 257-5547

**e-mail address of person responsible for this SDS** : MSDS@huntsman.com

**Emergency telephone number (24h/7day)** : Chemtrec: (800) 424-9300 or (703) 527-3887

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
SKIN SENSITIZATION - Category 1  
TOXIC TO REPRODUCTION [Fertility] - Category 1B  
AQUATIC HAZARD (LONG-TERM) - Category 3  
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 48.5%  
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 63.9%

#### GHS label elements

##### Hazard pictograms



## Section 2. Hazards identification

- Signal word** : Danger
- Hazard statements** : Causes serious eye damage.  
Causes skin irritation.  
May cause an allergic skin reaction.  
May damage fertility.  
Harmful to aquatic life with long lasting effects.
- Precautionary statements** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves: > 8 hours (breakthrough time): Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
Tetraethylenepentamine	3 - 7	112-57-2
Bisphenol A	3 - 7	80-05-7
Diethylenetriamine	1 - 3	111-40-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** :

## Section 4. First aid measures

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : May cause burns to mouth, throat and stomach.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

## Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

- Flash point** : Closed cup: >98°C (>208.4°F)

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides  
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

## Section 6. Accidental release measures

**Methods and materials for containment and cleaning up** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Diethylenetriamine	<b>ACGIH TLV (United States, 3/2012). Absorbed through skin.</b> TWA: 1 ppm 8 hours. TWA: 4.2 mg/m <sup>3</sup> 8 hours.

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure controls** :

## Section 8. Exposure controls/personal protection

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Thermal hazards** : Not available.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Paste.]
- Color** : Gray.
- Odor** : Ammoniacal.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/Freezing point** : Not available.
- Boiling/condensation point** : Not available.
- Flash point** : Closed cup: >98°C (>208.4°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.

## Section 9. Physical and chemical properties

<b>Lower and upper explosive (flammable) limits</b>	: Not available.
<b>Vapor pressure</b>	: Not available.
<b>Vapor density</b>	: Not available.
<b>Relative density</b>	: 0.69
<b>Solubility in water</b>	: Slightly soluble
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>Density</b>	: 0.6 to 0.74 g/cm <sup>3</sup> [25°C (77°F)]
<b>Viscosity</b>	: Not available.

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: No specific data.
<b>Incompatible materials</b>	: No specific data.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Endpoint	Species	Result
Tetraethylenepentamine	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit - Male, Female	1260 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	1716.2 mg/kg
Bisphenol A	No official guidelines	LD50 Oral	Rat - Male	3250 mg/kg
	Unknown guidelines	LC50 Inhalation Dusts and mists	Rat - Male, Female	>170 mg/m <sup>3</sup>
Diethylenetriamine	Unknown guidelines	LD50 Dermal	Rabbit - Male	6400 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	2000 to 5000 mg/kg
Diethylenetriamine	No official guidelines	LD50 Dermal	Rabbit	1045 mg/kg
	No official guidelines	LD50 Oral	Rat - Male	1620 mg/kg
	OECD 403 Acute Inhalation Toxicity	NOEC Inhalation Dusts and mists	Rat - Male, Female	0.07 mg/l

#### Irritation/Corrosion

## Section 11. Toxicological information

Product/ingredient name	Test	Species	Result
Tetraethylenepentamine	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Corrosive
Bisphenol A	Unknown guidelines	Rabbit	Eyes - Corrosive
	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Non-irritant.
Diethylenetriamine	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Severe irritant
	No official guidelines	Rabbit	Skin - Corrosive
	No official guidelines	Rabbit	Eyes - Corrosive

### Conclusion/Summary

<b>Skin</b>	:	Tetraethylenepentamine	Corrosive to the skin.
		Bisphenol A	Non-irritating to the skin.
		Diethylenetriamine	Corrosive to the skin.
<b>Eyes</b>	:	Tetraethylenepentamine	Corrosive to eyes.
		Bisphenol A	Severely irritating to eyes.
		Diethylenetriamine	Corrosive to eyes.
<b>Respiratory</b>	:	Tetraethylenepentamine	No additional information.
		Bisphenol A	No additional information.
		Diethylenetriamine	No additional information.

### Sensitization

Product/ingredient name	Test	Route of exposure	Species	Result
Tetraethylenepentamine	OECD 406 Skin Sensitization	skin	Guinea pig	Sensitizing
Bisphenol A	OECD 429 Skin Sensitization:	skin	Mouse	Not sensitizing
	Local Lymph Node Assay			
Diethylenetriamine	OECD 406 Skin Sensitization	skin	Guinea pig	Sensitizing
	No official guidelines	Respiratory	Mouse	Not sensitizing

### Mutagenicity

Product/ingredient name	Test	Result
Tetraethylenepentamine	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Positive
	Experiment: In vitro Subject: Mammalian-Animal Metabolic activation: +/-	Positive
	Experiment: In vitro Subject: Mammalian-Animal	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Bisphenol A	Experiment: In vitro Subject: bacteria/yeast Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative

## Section 11. Toxicological information

Diethylenetriamine	Experiment: In vivo Subject: Insect	Negative
	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

### Conclusion/Summary :

Tetraethylenepentamine The weight of the scientific evidence indicates that this material is non-genotoxic.  
Diethylenetriamine No mutagenic effect.

### Carcinogenicity

Product/ingredient name	Test	Species	Dose	Exposure	Result/Result type
Bisphenol A	-	Rat - Male, Female	-	103 weeks; 7 days per week	Negative - Oral - NOAEL
Diethylenetriamine	No official guidelines	Mouse - Male	56.3 mg/kg	3 days per week	Negative - Dermal - NOEL

### Conclusion/Summary :

Tetraethylenepentamine In accordance with column 2 of Annex VII - X of Regulation (EC) No 1907/2006, the test for this property of the substance does not need to be conducted.

### Reproductive toxicity

Product/ingredient name	Test	Species	Maternal toxicity	Fertility	Developmental effects
Bisphenol A	OECD 416 Two- Generation Reproduction Toxicity Study	Rat - Male, Female	Positive	Negative	Negative
Diethylenetriamine	OECD 421 Reproduction/ Developmental Toxicity Screening Test	Rat - Male, Female	Positive	Positive	Negative

### Teratogenicity

Product/ingredient name	Test	Species	Result/Result type
Tetraethylenepentamine	OECD 414 Prenatal Developmental Toxicity Study	Rat - Female	Negative - Oral
Bisphenol A	OECD 414 Prenatal Developmental Toxicity Study	Rabbit - Female	Negative - Dermal
	OECD 416 Two- Generation Reproduction Toxicity Study	Rat - Female	Negative - Oral

### Specific target organ toxicity (single exposure)

## Section 11. Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Bisphenol A	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : May cause burns to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.

## Section 11. Toxicological information

**Potential delayed effects** : Not available.

### Potential chronic health effects

Product/ingredient name	Test	Endpoint	Species	Result
Tetraethylenepentamine	No official guidelines	Sub-chronic NOAEL Oral	Rat - Male, Female	50 mg/kg/d
Bisphenol A	OECD 410 Repeated Dose Dermal Toxicity: 21/28-day Study	Sub-acute NOAEL Dermal	Rabbit - Male, Female	50 mg/kg/d
	OECD 407 Repeated Dose 28-day Oral Toxicity Study in Rodents	Sub-chronic LOAEL Oral	Rat - Male, Female	600 mg/kg
Diethylenetriamine	Unknown guidelines	Sub-chronic NOEC Inhalation Dusts and mists	Rat - Male, Female	10 mg/m <sup>3</sup>
	OECD	Sub-chronic NOEL Oral	Rat - Male, Female	70 to 80 mg/kg/d
	No official guidelines	Chronic NOAEL Dermal	Rat - Male, Female	114 mg/kg/d
	No official guidelines	Sub-acute NOEC Inhalation Vapor	Rat - Male, Female	550 mg/m <sup>3</sup>

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : May damage fertility.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	4728.3 mg/kg
Dermal	8987.7 mg/kg

**Other information** : Not available.

## Section 12. Ecological information

### Toxicity

## Section 12. Ecological information

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
Tetraethylenepentamine	No official guidelines	Acute EC50	2 hours Static	Bacteria	97.3 mg/l
	EU EC C.2 Acute Toxicity for Daphnia	Acute EC50	48 hours Static	Daphnia	24.1 mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute ErC50 (growth rate)	72 hours Static	Algae	6.8 mg/l
	EU EC C.1 Acute Toxicity for Fish	Acute LC50	96 hours Semi-static	Fish	420 mg/l
	No official guidelines	Chronic EC10	2 hours Static	Bacteria	46 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOEC	72 hours Static	Algae	0.5 mg/l
Bisphenol A	-	Acute EC50	96 hours	Algae	2.5 to 3.1 mg/l
	-	Acute EC50	48 hours	Daphnia	3.9 to 10.2 mg/l
	-	Acute LC50	96 hours	Fish	7.5 mg/l
	EPA OPPTS	Chronic NOEC	444 days Flow-through	Fish	0.016 mg/l
Diethylenetriamine	No official guidelines	Acute EC50	48 hours Static	Daphnia	32 mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute EbC50 (biomass)	72 hours Static	Algae	1164 mg/l
	EU EC C.1 Acute Toxicity for Fish	Acute LC50	96 hours Semi-static	Fish	430 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOEC	72 hours Static	Algae	10 mg/l
	No official guidelines	Chronic NOEC	3 hours Static	Bacteria	6 mg/l
	EU	Chronic NOEC	21 days Semi-static	Daphnia	5.6 mg/l
	OECD OECD 210 - Fish, Early-Life Stage Toxicity Test	Chronic NOEC	28 days Semi-static	Fish	10 mg/l

### Persistence and degradability

Product/ingredient name	Test	Period	Result
Tetraethylenepentamine	OECD 302A Inherent Biodegradability: Modified SCAS Test	84 days	17 %
Bisphenol A	-	28 days	1 to 2 %
Diethylenetriamine	OECD 301D Ready Biodegradability - Closed Bottle Test	21 days	87 %

**Conclusion/Summary** : Tetraethylenepentamine Not biodegradable  
Diethylenetriamine Readily biodegradable

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Tetraethylenepentamine	-	-	Not readily
Bisphenol A	-	-	Not readily
Diethylenetriamine	-	50%; 0.11 day(s)	Readily

## Section 12. Ecological information

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Tetraethylenepentamine	-3.16	-	low
Diethylenetriamine	-1.58	0.3 to 6.3	low

### Mobility in soil

Not available.

**Other adverse effects** : No known significant effects or critical hazards.

### Other ecological information

**BOD5** : Not determined.

**COD** : Not determined.

**TOC** : Not determined.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## Section 14. Transport information

### Proper shipping name





**DOT** : Polyamines, liquid, corrosive, n.o.s. (TETRAETHYLENEPENTAMINE, DIETHYLENETRIAMINE)

**TDG** : Polyamines, liquid, corrosive, n.o.s. (TETRAETHYLENEPENTAMINE, DIETHYLENETRIAMINE)

**IMDG** : Polyamines, liquid, corrosive, n.o.s. (TETRAETHYLENEPENTAMINE, DIETHYLENETRIAMINE)

**IATA** : Polyamines, liquid, corrosive, n.o.s. (TETRAETHYLENEPENTAMINE, DIETHYLENETRIAMINE)

## Section 14. Transport information

Regulatory information	UN number	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	UN2735	8	II		-
<b>TDG Classification</b>	UN2735	8	II		-
<b>IMDG Classification</b>	UN2735	8	II		<b>Emergency schedules (EmS)</b> F-A, S-B
<b>IATA Classification</b>	UN2735	8	II		<b>Passenger and Cargo Aircraft</b> Quantity limitation: 1 L Packaging instructions: 851 <b>Cargo Aircraft Only</b> Quantity limitation: 30 L Packaging instructions: 855

PG\* : Packing group

## Section 15. Regulatory information

### Safety, health and environmental regulations specific for the product

#### United States Regulations

**TSCA 8(b) inventory** : All components are listed or exempted.

**TSCA 5(a)2 final significant new use rule (SNUR)** : No ingredients listed.

**TSCA 5(e) substance consent order** : No ingredients listed.

**TSCA 12(b) export notification** : No ingredients listed.

**SARA 311/312** : Immediate (acute) health hazard  
Delayed (chronic) health hazard

**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)** : No ingredients listed.

**Clean Air Act - Ozone Depleting Substances (ODS)** : This product does not contain nor is it manufactured with ozone depleting substances.

## Section 15. Regulatory information

**SARA 313**  
**Form R - Reporting requirements**

<u>Product name</u>	<u>Concentration %</u>
: Bisphenol A	4.348

<u>Ingredient name</u>	<u>%</u>	<u>Section 304 CERCLA Hazardous Substance</u>	<u>CERCLA Reportable Quantity (Lbs)</u>	<u>Product Reportable Quantity (Lbs)</u>
CERCLA Hazardous substances				
: Phenol	0.0013405	Listed	1000	74599030
: Formaldehyde	0.00013405	Listed	100	74599030

### State regulations

**PENNSYLVANIA - RTK** : SILICA , TETRAETHYLENEPENTAMINE, Bisphenol A, Diethylenetriamine

**California Prop 65** : **WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>
Formaldehyde	Yes.	No.

### Canadian regulations

**CEPA DSL** : All components are listed or exempted.

**WHMIS Classes** : Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).  
Class E: Corrosive material

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.**

### Brazil Regulations

**Classification system used** : Norma ABNT-NBR 14725-2:2012

### International lists

: **Australia inventory (AICS):** At least one component is not listed.  
: **China inventory (IECSC):** All components are listed or exempted.  
: **Japan inventory:** At least one component is not listed.  
: **Korea inventory:** All components are listed or exempted.  
: **Malaysia Inventory (EHS Register):** Not determined.  
: **New Zealand Inventory of Chemicals (NZIoC):** At least one component is not listed.  
: **Philippines inventory (PICCS):** At least one component is not listed.  
: **Taiwan inventory (CSNN):** Not determined.

## Section 16. Other information


**Hazardous Material  
Information System (U.S.A.)** :

<b>Health</b>	*	3
<b>Flammability</b>		1
<b>Physical hazards</b>		0
<b>Personal protection</b>		

**The customer is responsible for determining the PPE code for this material.**

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**National Fire Protection  
Association (U.S.A.)** :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Date of printing** : 12/6/2013.  
**Date of issue** : 12/6/2013.  
**Date of previous issue** : 12/6/2013.  
**Version** : 4

📌 Indicates information that has changed from previously issued version.

### Notice to reader

**While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.**

**IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.**

**THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.**

**Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent**

## Section 16. Other information

*upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.*

**NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.**