



Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name ADH 1007M LB
Product Code L1007M
Product(s) Covered See section 16 for more information

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use Adhesives.
Uses Advised Against No information available

1.3. Details of the Supplier of the Safety Data Sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1 (800) 843-0844 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)
Fax: +1 (414) 774-8075

E-mail msds@bostik-us.com

1.4. Emergency Telephone Number

Telephone: 1-800-227-0332
(Outside U.S.) 1-703-527-3887

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the Substance or Mixture

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

2.2. Label Elements

EMERGENCY OVERVIEW

DANGER

Hazard statements
Causes skin irritation

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Appearance No information available **Physical State** Liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see first aid measures on this label)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
In case of fire: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

Not applicable

Unknown acute toxicity

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

29% of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

May be harmful if swallowed.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	CAS No.	Weight-%
Ethyl acetate	141-78-6	15 - 40
Toluene	108-88-3	10 - 30
Methyl ethyl ketone	78-93-3	7 - 13
Rosin	8050-09-7	3 - 7
Solvent naphtha, petroleum, light aliphatic	64742-89-8	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Ethylbenzene	100-41-4	0.1 - 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General Advice	If medical advice is needed, have product container or label at hand.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/ attention. May cause sensitization by skin contact.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
Self-protection of the First Aider	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians May cause sensitization by skin contact. Treat symptomatically.

4.4. Reference to Other Sections

Reference to Other Sections See Section 12: ECOLOGICAL INFORMATION

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media

Use CO2, dry chemical, or foam. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media

Use water spray or fog; do not use straight streams.

5.2. Special Hazards Arising from the Substance or Mixture

Specific Hazards Arising from the Chemical

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

May be ignited by friction, heat, sparks or flames.

5.3. Advice for Firefighters

Protective Equipment and Precautions for Firefighters

Move containers from fire area if you can do it without risk. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.

Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

For Emergency Responders

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Environmental Precautions

Environmental Precautions

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. See Section 12 for additional Ecological Information.

6.3. Methods and Material for Containment and Cleaning up

Methods for Containment

Dike far ahead of spill; use dry sand to contain the flow of material. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for Cleaning up

Use personal protective equipment as required. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Use clean non-sparking tools to collect absorbed material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

6.4. Reference to other sections

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Reference to Other Sections See Section 12: ECOLOGICAL INFORMATION
Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Advice on Safe Handling Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take precautionary measures against static charges. Use explosion-proof electrical/ventilating/lighting/equipment. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Avoid breathing vapors or mists.

7.2. Conditions for Safe Storage, including any Incompatibilities

Storage Conditions Keep only in the original container/package in a cool well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible Materials Strong acids and bases.

7.3. Specific End Use(s)

Other Information No information available.

7.4. References to Other Sections

Reference to Other Sections See Section 12: ECOLOGICAL INFORMATION
Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Ethyl acetate 141-78-6	TWA: 400 ppm	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³	TWA: 400 ppm TWA: 1400 mg/m ³	TWA: 400 ppm TWA: 1400 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³	TWA: 200 ppm Ceiling: 300 ppm	TWA: 50 ppm TWA: 188 mg/m ³
Methyl ethyl ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	TWA: 200 ppm TWA: 590 mg/m ³	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
Rosin 8050-09-7	-	TWA: 0.1 mg/m ³ Formaldehyde	-	TWA: 0.1 mg/m ³
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	-	TWA: 100 ppm TWA: 435 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³
Ethylbenzene	TWA: 20 ppm	IDLH: 800 ppm	TWA: 100 ppm	TWA: 100 ppm

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

100-41-4		TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	TWA: 435 mg/m ³	TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
----------	--	--	----------------------------	--

Chemical Name	Argentina	Brazil	Chile	Venezuela
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 310 ppm TWA: 1090 mg/m ³	TWA: 350 ppm TWA: 1260 mg/m ³	STEL: 15 ppm TWA: 400 ppm
Toluene 108-88-3	TWA: 50 ppm Skin	TWA: 78 ppm TWA: 290 mg/m ³ Skin	TWA: 80 ppm TWA: 300 mg/m ³ Skin	Skin TWA: 20 ppm
Methyl ethyl ketone 78-93-3	TWA: 200 ppm STEL: 300 ppm	TWA: 155 ppm TWA: 460 mg/m ³	TWA: 160 ppm TWA: 472 mg/m ³	STEL: 300 ppm TWA: 200 ppm
Rosin 8050-09-7	-	-	-	TWA:
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 78 ppm TWA: 340 mg/m ³	TWA: 80 ppm TWA: 347 mg/m ³	Skin STEL: 150 ppm TWA: 100 ppm
Ethylbenzene 100-41-4	TWA: 100 ppm STEL: 125 ppm	TWA: 78 ppm TWA: 340 mg/m ³	TWA: 80 ppm TWA: 348 mg/m ³	Skin STEL: 125 ppm TWA: 100 ppm

8.2. Exposure Controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Showers
Eyewash stations
Ventilation systems.

Personal protective equipment [PPE]

Eye/Face Protection

Tight sealing safety goggles. Face protection shield.

Skin and Body Protection

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Wash face, hands and any exposed skin thoroughly after handling. Take off all contaminated clothing and wash it before reuse. Regular cleaning of equipment, work area and clothing is recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Color	Amber
Odor	Solvent
Odor Threshold	No information available

Property

Values

Remarks • Method

pH	No information available	
Melting Point/Freezing Point	No information available	
Boiling Point	> 77 °C / 170.6 °F	
Flash Point	-6.7 °C / = 20 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	Not applicable for liquids
Flammability Limit in Air		

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Upper Flammability Limit	No information available
Lower Flammability Limit	No information available
Vapor Pressure	No information available
Vapor Density	No information available
Relative Density	No information available
Water Solubility	No information available
Solubility in Other Solvents	
Partition Coefficient	No information available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Kinematic Viscosity	No information available
Dynamic Viscosity	No information available
Explosive Properties	No information available
Oxidizing Properties	No information available
9.2. Other Information	
Softening Point	No information available
Molecular Weight	No information available
Solvent Content (%)	No information available
Solid Content (%)	25.0
Density	.930 g/ml
VOC	360.0 g/L

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended storage conditions.

10.2. Chemical Stability

Stable under recommended storage conditions.

10.3. Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to Avoid

Keep away from heat, sparks and flames.

10.5. Incompatible Materials

Strong acids and bases.

10.6. Hazardous Decomposition Products

Carbon oxides.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on Toxicological Effects

Product Information	No Data Available
Inhalation	No Data Available.

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Eye contact No Data Available.
Skin Contact No Data Available.
Ingestion No Data Available.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit) > 20 mL/kg (Rabbit)	LC0 29.3 mg/l air
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	> 20 mg/L (Rat) 4 h
Methyl ethyl ketone 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Rosin 8050-09-7	>2800 mg/Kg (rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
Solvent naphtha, petroleum, light aliphatic 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= >47635 mg/L (Rat) 4 h = >5000 ppm (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 1432 mg/L (Rat) 4 h

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Symptoms No information available.
Skin Corrosion/Irritation No information available.
Serious Eye Damage/Eye Irritation No information available.
Irritation No information available.
Corrosivity No information available.
Sensitization No information available.
Germ Cell Mutagenicity No information available.
Reproductive Toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.
Developmental Toxicity No information available.
Teratogenicity No information available.
STOT - Single Exposure No information available.
STOT - Repeated Exposure No information available.
Chronic Toxicity Contains a known or suspected reproductive toxin. May cause adverse liver effects. Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure.
Target Organ Effects Central nervous system, Eyes, Kidney, Liver, Respiratory system, Skin, Thyroid.
Aspiration Hazard No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3	-	Group 3	-	-
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Confirmed animal carcinogen with unknown relevance to humans
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Ethyl acetate 141-78-6	EC50 48 h = 3300 mg/L (Desmodesmus subspicatus)	LC50 96 h 220 - 250 mg/L (Pimephales promelas flow-through) LC50 96 h = 484 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h 352 - 500 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50 48 h = 560 mg/L (Daphnia magna Static)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50 48 h 5.46 - 9.83 mg/L (Daphnia magna Static) EC50 48 h = 11.5 mg/L (Daphnia magna)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50 96 h 3130 - 3320 mg/L (Pimephales promelas flow-through)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)
Rosin 8050-09-7	EC50 72 h = 400 mg/L (Desmodesmus subspicatus)	LC50 (96h) >10mg/L Fish (Danio rerio)	EC50 = 31.5 mg/L 30 min	EC50 48 h >100 mg/L (Daphnia magna)
Solvent naphtha, petroleum, light aliphatic 64742-89-8	EC50 72 h = 4700 mg/L (Pseudokirchneriella subcapitata)			
Xylenes (o-, m-, p- isomers) 1330-20-7		LC50 96 h 13.5 - 17.3 mg/L (Oncorhynchus mykiss)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (water flea)
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h 1.8 - 2.4 mg/L (Daphnia magna)

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulative Potential

No information available.

12.4. Mobility in Soil

No information available.

12.5 Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Disposal of Wastes

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Contaminated Packaging Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORTATION INFORMATION

DOT

UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II
Reportable Quantity (RQ) (Toluene: RQ (kg)= 0.454, 2-Chloro-1,3-butadiene: RQ (kg)= 0.454, Xylenes (o-, m-, p-isomers): RQ (kg)= 45.40, Ethyl acetate: RQ (kg)= 2270.00, Methyl ethyl ketone: RQ (kg)= 2270.00)
Special Provisions 149, B52, IB2, T4, TP1, TP8
Description UN1133, Adhesives, 3, II
Emergency Response Guide Number 128

IATA

UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II
ERG Code 3L
Special Provisions A3
Description UN1133, Adhesives, 3, II

IMDG

UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II
EmS-No F-E, S-D
Description UN1133, Adhesives, 3, II, (-6.7°C c.c.)

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 - Flammable liquid

D2A - Very toxic materials

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2



United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.
Toluene	108-88-3
Xylenes (o-, m-, p- isomers)	1330-20-7
Ethylbenzene	100-41-4

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	yes
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

California Proposition 65

This product contains one or more of the substances listed on Proposition 65 at or above 0.01 wt. %

Chemical Name	CAS No.
Toluene	108-88-3
Ethylbenzene	100-41-4
Cumene	98-82-8

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Product(s) Covered

L1007M-59	LIQ. 1007M MP38.78LB(5GL)/P18
L1007M-59V	LIQ. 1007M MP38.78LB(5GL)/P18
L1007M-82	LIQ. 1007M RC2.3LB(1QT)
L1007M-OH	LIQ. 1007M MD(54GL)421.2/P4
L1007M-OHV	LIQ. 1007M MD421.2LB VARWT

HMIS Health Hazards 2* Flammability 3 Physical Hazards 0 Personal Protection X

Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

Safety Data Sheet

L1007M
ADH 1007M LB

Revision Date 27-Apr-2017
Supersedes Date: 10-Feb-2014
Version 2

Key Literature References and Sources for Data

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision Date	27-Apr-2017
Revision Note	SDS sections updated, 1, 2, 4, 5, 6, 7, 8, 11, 12, 14, 15, 16.
Training Advice	Provide adequate information, instruction, and training for operator
Additional information	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet